FEDERAL PROJECT	STATE PROJECT	PARISH	SHEET NO.

OPENING					H	E	C	J	D	L	M	S	BARS E								#4 BARS J				BARS O				#4 BARS P		#4BARS H		#4BARS V		BARS M		CONC.	STEEL	OPENING				
Eq. Dia. in.	Span in.	Rise in.	No.	Area sq.ft.	Lgth. ft.in.	Lgth. ft.in.	Lgth. ft.in.	Lgth. ft.in.	Lgth. ft.in.	Lgth. ft.in.	Lgth. ft.in.	Lgth. ft.in.	Size	No.	Lgth. ft.in.	Spc. in.	X ft.in.	Y ft.in.	Z ft.in.	No.	Lgth. ft.in.	Size	No.	Lgth. ft.in.	Spc. in.	No.	Lgth. ft.in.	No.	Lgth. ft.in.	No.	Lgth. ft.in.	Size	No.	Lgth. ft.in.	CU. YDS.	LBS.	Area sq.ft.	No.	Rise in.	Span in.	Eq. Dia. in.
15	17	13	1	1.1	2- 1	0- 4	0- 6	2-10	0-10	5-11	13-10	1- 3	4	14	2-11	12.0	0- 5	2	2- 4	2	5- 7	4	15	3- 4	12.0	7	13- 6	0	0- 0	1	8	4	2	13- 6	2.52	150	1.1	1	13	17	15
15	17	13	2	2.2	2- 1	0- 4	0- 6	2-10	0-10	5-11	17- 7	1- 3	4	17	2-11	12.0	0- 5	2	2- 4	2	5- 7	4	18	3- 4	12.0	7	17- 3	1	1- 5	2	8	4	2	17- 3	3.18	186	2.2	2	13	17	15
15	17	13	3	3.3	2- 1	0- 4	0- 6	2-10	0-10	5-11	21- 4	1- 3	4	20	2-11	12.0	0- 5	2	2- 4	2	5- 7	4	22	3- 4	12.0	7	21- 0	2	1- 5	3	8	4	2	21- 0	3.84	225	3.3	3	13	17	15
15	17	13	4	4.4	2- 1	0- 4	0- 6	2-10	0-10	5-11	25- 1	1- 3	4	23	2-11	12.0	0- 5	2	2- 4	2	5- 7	4	26	3- 4	12.0	7	24- 9	3	1- 5	4	8	4	2	24- 9	4.50	264	4.4	4	13	17	15
15	17	13	5	5.5	2- 1	0- 4	0- 6	2-10	0-10	5-11	28-10	1- 3	4	26	2-11	12.0	0- 5	2	2- 4	2	5- 7	4	30	3- 4	12.0	7	28- 6	4	1- 5	5	8	4	2	28- 6	5.16	302	5.5	5	13	17	15
15	17	13	6	6.6	2- 1	0- 4	0- 6	2-10	0-10	5-11	32- 7	1- 3	4	29	2-11	12.0	0- 5	2	2- 4	2	5- 7	4	33	3- 4	12.0	7	32- 3	5	1- 5	6	8	4	2	32- 3	5.83	339	6.6	6	13	17	15
18	21	15	1	1.6	2- 3	0- 4	0- 6	2-11	0-10	6- 4	15- 2	1- 3	4	14	3- 1	12.0	0- 5	2	2- 6	2	6- 0	4	16	3- 5	12.0	7	14-10	0	0- 0	2	8	4	2	14-10	2.84	163	1.6	1	15	21	18
18	21	15	2	3.2	2- 3	0- 4	0- 6	2-11	0-10	6- 4	19- 4	1- 3	4	17	3- 1	12.0	0- 5	2	2- 6	2	6- 0	4	20	3- 5	12.0	7	19- 0	1	1- 5	4	8	4	2	19- 0	3.59	206	3.2	2	15	21	18
18	21	15	3	4.8	2- 3	0- 4	0- 6	2-11	0-10	6- 4	23- 7	1- 3	4	20	3- 1	12.0	0- 5	2	2- 6	2	6- 0	4	24	3- 5	12.0	7	23- 3	2	1- 5	6	8	4	2	23- 3	4.35	248	4.8	3	15	21	18
18	21	15	4	6.4	2- 3	0- 4	0- 6	2-11	0-10	6- 4	27-10	1- 3	4	23	3- 1	12.0	0- 5	2	2- 6	2	6- 0	4	29	3- 5	12.0	7	27- 6	3	1- 5	8	8	4	2	27- 6	5.11	293	6.4	4	15	21	18
18	21	15	5	8.0	2- 3	0- 4	0- 6	2-11	0-10	6- 4	32- 0	1- 3	4	26	3- 1	12.0	0- 5	2	2- 6	2	6- 0	4	33	3- 5	12.0	7	31- 8	4	1- 5	10	8	4	2	31- 8	5.86	335	8.0	5	15	21	18
18	21	15	6	9.6	2- 3	0- 4	0- 6	2-11	0-10	6- 4	36- 3	1- 3	4	29	3- 1	12.0	0- 5	2	2- 6	2	6- 0	4	37	3- 5	12.0	7	35-11	5	1- 5	12	8	4	2	35-11	6.63	378	9.6	6	15	21	18
24	28	20	1	2.9	2- 8	0- 5	0- 6	3- 1	0-10	7- 7	18- 6	1- 3	4	16	3- 7	12.0	0- 6	2	2-11	4	7- 3	4	19	3- 8	12.0	7	18- 2	0	0- 0	3	8	4	2	18- 2	3.72	215	2.9	1	20	28	24
24	28	20	2	5.8	2- 8	0- 5	0- 6	3- 1	0-10	7- 7	23- 6	1- 3	4	19	3- 7	12.0	0- 6	2	2-11	4	7- 3	4	24	3- 8	12.0	7	23- 2	1	1- 5	6	8	4	2	23- 2	4.67	267	5.8	2	20	28	24
24	28	20	3	8.7	2- 8	0- 5	0- 6	3- 1	0-10	7- 7	28- 7	1- 3	4	22	3- 7	12.0	0- 6	2	2-11	4	7- 3	4	29	3- 8	12.0	7	28- 3	4	1- 5	9	8	4	2	28- 3	5.64	321	8.7	3	20	28	24
24	28	20	4	11.6	2- 8	0- 5	0- 6	3- 1	0-10	7- 7	33- 7	1- 3	4	25	3- 7	12.0	0- 6	2	2-11	4	7- 3	4	34	3- 8	12.0	7	33- 3	6	1- 5	12	8	4	2	33- 3	6.59	373	11.6	4	20	28	24
24	28	20	5	14.5	2- 8	0- 5	0- 6	3- 1	0-10	7- 7	38- 8	1- 3	4	28	3- 7	12.0	0- 6	2	2-11	4	7- 3	4	39	3- 8	12.0	7	38- 4	8	1- 5	15	8	4	2	38- 4	7.56	427	14.5	5	20	28	24
24	28	20	6	17.4	2- 8	0- 5	0- 6	3- 1	0-10	7- 7	43- 9	1- 3	4	31	3- 7	12.0	0- 6	2	2-11	4	7- 3	4	43	3- 8	12.0	7	43- 5	10	1- 5	18	8	4	2	43- 5	8.52	480	17.4	6	20	28	24
30	35	24	1	4.5	3- 0	0- 5	0- 6	3- 3	0-10	8- 6	21- 1	1- 3	4	18	3-11	12.0	0- 6	2	2- 3	4	8- 2	4	22	3-10	12.0	7	20- 9	0	0- 0	3	8	4	2	20- 9	4.45	251	4.5	1	24	35	30
30	35	24	2	9.0	3- 0	0- 5	0- 6	3- 3	0-10	8- 6	27- 0	1- 3	4	21	3-11	12.0	0- 6	2	2- 3	4	8- 2	4	23	3-10	12.0	7	26- 8	2	1- 5	6	8	4	2	26- 8	5.61	313	9.0	2	24	35	30
30	35	24	3	13.5	3- 0	0- 5	0- 6	3- 3	0-10	8- 6	32-10	1- 3	4	24	3-11	12.0	0- 6	2	2- 3	4	8- 2	4	34	3-10	12.0	7	32- 6	4	1- 5	9	8	4	2	32- 6	6.76	375	13.5	3	24	35	30
30	35	24	4	18.0	3- 0	0- 5	0- 6	3- 3	0-10	8- 6	38- 9	1- 3	4	27	3-11	12.0	0- 6	2	2- 3	4	8- 2	4	39	3-10	12.0	7	38- 5	6	1- 5	12	8	4	2	38- 5	7.92	434	18.0	4	24	35	30
30	35	24	5	22.5	3- 0	0- 5	0- 6	3- 3	0-10	8- 6	44- 7	1- 3	4	30	3-11	12.0	0- 6	2	2- 3	4	8- 2	4	45	3-10	12.0	7	44- 3	8	1- 5	15	8	4	2	44- 3	9.06	496	22.5	5	24	35	30
30	35	24	6	27.0	3- 0	0- 5	0- 6	3- 3	0-10	8- 6	50- 6	1- 3	4	33	3-11	12.0	0- 6	2	2- 3	4	8- 2	4	51	3-10	12.0	7	50- 2	10	1- 5	18	8	4	2	50- 2	10.23	558	27.0	6	24	35	30
36	42	29	1	6.5	3- 5	0- 6	0- 6	3- 6	0-10	9- 8	24- 3	1- 3	4	20	4- 5	12.0	0- 7	2	3- 8	4	9- 4	4	25	4- 2	12.0	7	23-11	0	0- 0	4	8	4	2	23-11	5.52	299	6.5	1	29	42	36
36	42	29	2	13.0	3- 5	0- 6	0- 6	3- 6	0-10	9- 8	31- 0	1- 3	4	23	4- 5	12.0	0- 7	2	3- 8	4	9- 4	4	32	4- 2	12.0	7	30- 8	2	1- 5	8	8	4	2	30- 8	6.93	372	13.0	2	29	42	36
36	42	29	3	19.5	3- 5	0- 6	0- 6	3- 6	0-10	9- 8	37- 8	1- 3	4	26	4- 5	12.0	0- 7	2	3- 8	4	9- 4	4	38	4- 2	12.0	7	37- 4	4	1- 5	12	8	4	2	37- 4	8.32	441	19.5	3	29	42	36
36	42	29	4	26.0	3- 5	0- 6	0- 6	3- 6	0-10	9- 8	44- 5	1- 3	4	29	4- 5	12.0	0- 7	2	3- 8	4	9- 4	4	45	4- 2	12.0	7	44- 1	6	1- 5	16	8	4	2	44- 1	9.74	514	26.0	4	29	42	36
36	42	29	5	32.5	3- 5	0- 6	0- 6	3- 6	0-10	9- 8	51- 1	1- 3	4	32	4- 5	12.0	0- 7	2	3- 8	4	9- 4	4	52	4- 2	12.0	7	50- 9	8	1- 5	20	8	4	2	50- 9	11.13	586	32.5	5	29	42	36
36	42	29	6	39.0	3- 5	0- 6	0- 6	3- 6	0-10	9- 8	57- 9	1- 3	4	35	4- 5	12.0	0- 7	2	3- 8	4	9- 4	4	58	4- 2	12.0	7	57- 5	10	1- 5	24	8	4	2	57- 5	12.52	655	39.0	6	29	42	36
42	49	33	1	8.9	3- 9	0- 7	0- 6	3- 7	0-10	10- 7	26-11	1- 5	4	22	4-10	12.0	0- 8	2	4- 0	6	10- 3	4	28	4- 4	12.0	8	26- 7	0	0- 0	5	8	4	2	26- 7	6.38	373	8.9	1	33	49	42
42	49	33	2	17.8	3- 9	0- 7	0- 6	3- 7	0-10	10- 7	34- 9	1- 5	4	25	4-10	12.0	0- 8	2	4- 0	6	10- 3	4	35	4- 4	12.0	8	34- 5	3	1- 8	10	8	4	2	34- 5	8.08	461	17.8	2	33	49	42
42	49	33	3	26.7	3- 9	0- 7	0- 6	3- 7	0-10	10- 7	42- 6	1- 5	4	28	4-10	12.0	0- 8	2	4- 0	6	10- 3	4	43	4- 4	12.0	8	42- 2	6	1- 8	15	8	4	2	42- 2	9.75	551	26.7	3	33	49	42
42	49	33	4	35.6	3- 9	0- 7	0- 6	3- 7	0-10	10- 7	50- 3	1- 5	4	31	4-10	12.0	0- 8	2	4- 0	6	10- 3	4	51	4- 4	12.0	8	49-11	9	1- 8	20	8	4	2	49-11	11.42	641	35.6	4	33	49	42
42	49	33	5	44.5	3- 9	0- 7	0- 6	3- 7	0-10	10- 7	58- 0	1- 5	4	34	4-10	12.0	0- 8	2	4- 0	6	10- 3	4	59	4- 4	12.0	8	57- 8	12	1- 8	25	8	4	2	57- 8	13.09	731	44.5	5	33	49	42
42	49	33	6	53.4	3- 9	0- 7	0- 6	3- 7	0-10	10- 7	65-10	1- 5	4	37	4-10	12.0	0- 8	2	4- 0	6	10- 3	4	67	4- 4	12.0	8	65- 6	15	1- 8	30	8	4	2	65- 6	14.79	822	53.4	6	33	49	42
48	57	38	1	11.6	4- 2	0- 7	0- 6	3-10	0-10	11- 9	30- 3	1- 8	4	30	5- 3	10.0	0- 8	2	4- 5	6	11- 5	4	31	4- 7	12.0	8	29-11	0	0- 0	6	8	4	2	29-11	7.60	448	11.6	1	38	57	48
48	57	38	2	23.2	4- 2	0- 7	0- 6	3-10	0-10	11- 9	39- 3	1- 8	4	33	5- 3	10.0	0- 8	2	4- 5	6	11- 5	4	40	4- 7	12.0	8	38-11	3	2- 0	12	8	4	2	38-11	9.65	553	23.2	2	38	57	48
48	57	38	3	34.8	4- 2	0- 7	0- 6	3-10	0-10	11- 9	48- 4	1- 8	4	36	5- 3	10.0	0- 8	2	4- 5	6	11- 5	4	49	4- 7	12.0	8	48- 0	6	2- 0	18	8	4	2	48- 0	11.72	659	34.8	3	38	57	48
48	57	38	4	46.4	4- 2	0- 7	0- 6	3-10	0-10	11- 9	57- 4	1- 8	4	39	5- 3	10.0	0- 8	2	4- 5	6	11- 5	4	58	4- 7	12.0	8	57- 0	9	2- 0	24	8	4	2	57- 0	13.76	763	46.4	4	38	57	48
48	57	38	5	58.0	4- 2	0- 7	0- 6	3-10	0-10	11- 9	66- 5	1- 8	4	42	5- 3	10.0	0- 8	2	4- 5	6	11- 5	4	67	4- 7	12.0	8	66- 1	12	2- 0	30	8	4	2	66- 1	15.83	869	58.0	5	38	57	48
48	57	38	6	69.6	4- 2	0- 7	0- 6	3-10	0-10	11- 9	75- 6	1- 8	4	45	5- 3	10.0	0- 8	2	4- 5	6	11- 5	4	76	4- 7	12.0	8	75- 2	15	2- 0	36	8	4	2	75- 2	17.90	974	69.6	6	38	57	48
54	64	43	1	14.7	4- 7	0- 8	0- 6	4- 0	0-10	13- 0	33- 7	1-10	4	40	5- 9	8.0	0- 9	2	4-10	8	12- 8	4	34	4-10	12.0	8	33- 3	0	0- 0	7	8	4	2	33- 3	8.91	556	14.7	1	43	64	54
54	64	43	2	29.4	4- 7	0- 8	0- 6	4- 0	0-10	13- 0	43- 8	1-10	4	44	5- 9	8.0	0- 9	2	4-10	8	12- 8	4	44	4-10	12.0	8	43- 4	4	2- 3	14	8	4	2	43- 4	11.31	680	29.4	2	43	64	54
54	64	43	3	44.1	4- 7	0- 8	0- 6	4- 0	0-10	13- 0	53-10	1-10	4	48	5- 9	8.0	0- 9	2	4-10	8	12- 8	4	55	4-10	12.0	8	53- 6	8	2- 3	21	8	4	2	53- 6	13.74	808	44.1	3	43	64	54
54	64	43	4	58.8	4- 7	0- 8	0- 6	4- 0	0-10	13- 0	63-11	1-10	4	52	5- 9	8.0	0- 9	2	4-10	8	12- 8	4	65	4-10	12.0	8	63- 7	12	2- 3	28	8	4	2	63- 7	16.15	932	58.8	4	43	64	54
54	64	43	5	73.5	4- 7	0- 8	0- 6	4- 0	0-10	13- 0	74- 1	1-10	4	56	5- 9	8.0	0- 9	2	4-10	8	12- 8	4	75	4-10	12.0	8	73- 9	16	2- 3	35	8	4	2	73- 9	18.57	1057	73.5	5	43	64	54
54	64	43	6	88.2	4- 7	0- 8	0- 6	4- 0	0-10	13- 0	84- 2	1-10	4	60	5- 9	8.0	0- 9	2	4-10	8	12- 8	4	85	4-10	12.0	8	83-10	20	2- 3	42	8	4	2	83-10	20.98	1181	88.2	6	43	64	54



PLAN



ELEVATION



BARS E



SECTION A-A



SECTION B-B

GENERAL NOTES

DESIGN: Method- Headwalls are designed as retaining walls according to current AASHTO working stress procedures. Walls are designed for a lateral earth pressure of 40 psf with 2.0 feet of surcharge. Overturning- A minimum safety factor of 2.0 is provided against overturning. The resultant of loads is within the middle third of the footing. Sliding - A minimum safety factor of 1.5 is provided against sliding. The coefficient of friction between the footing and soil is 0.5. Foundation - The design soil bearing pressure is 1800 psf. When strength of the soil at the site is less than 1800 psf, bedding material shall be added under the footing as directed.

MATERIALS: Concrete- All concrete shall be class A. All exposed edges shall be ¾ inch chamfered. Reinforcing Steel - Reinforcement shall be Grade 60. Bar spacing dimensions are to bar centers. Steel required for lap splices not detailed shall not be measured for payment. Reinforcing steel shall have 2" cover unless otherwise specified. Steel and concrete quantities shown in table are for one headwall.

A 1'-6" square of geotextile fabric (see Section 1019 of the LA DOTD Standard Specifications) shall be placed in contact with concrete behind each weephole in addition to approximately 2 cu.ft. of concrete sand (see Section 1003.02 of the LA DOTD Standard Specifications).

CONSTRUCTION JOINTS: All construction joints shown are optional. For details of keyed construction joints see Standard Plan CM-49. For construction joints without key, the joint surface shall be roughened. Hardened surface shall be cleaned. Immediately before new concrete is placed, joint surface shall be saturated with water.

STATE OF LOUISIANA
WILLIAM M. RAY
REG. No. 24936
REGISTERED PROFESSIONAL ENGINEER IN CIVIL ENGINEERING
William M. Ray
7-26-01

DATE	DESCRIPTION	BY
11-14-97	Revised General Notes And Assigned Name HW45CMPA1	JCM

REVISIONS

SPECIAL DETAIL NO. HW45CMPA1 — SHEET 1 OF 1

STRAIGHT HEADWALL FOR CMPA ON A 45° CROSSING 15" EQUIV. THRU 54" EQUIV.

DATED January 6, 1993

STATE OF LOUISIANA
DEPARTMENT OF TRANSPORTATION AND DEVELOPMENT

DESIGNED PAA	DETAILED KAJ	DIR. spdetail/headwall/
CHECKED	CHECKED PAA	FILE HW45cmpa.dgn

HYDRAULICS SECTION

PRELIMINARY NOT FOR CONSTRUCTION PURPOSES ONLY

28-NOV-2007 11:00
R:\Standard Plans\Special Details\English\Old Sheets\HW45CMPA1.dgn